



Industrial Mother Board

IM-G41DI

Intel® Core™ 2 Duo Desktop Processor based ATX Industrial Motherboard with 2 ISA, 4 PCI, VGA, Dual Gigabit Ethernet, SATA, Audio, COM & USB



Core Specifications

- Intel® Core™ 2 Quad, Core2 Duo Desktop® Pentium Dual Core, Pentium D Processor in an LGA775 Socket
- Intel® G41 Chipset, 1333/1066/800 MHz FSB
- Dual-channel DDR3 Memory Architecture
- Integrated Intel® GMA X4500 Graphics
- Dual Gigabit Ethernet
- Four SATA 300 MB/s Ports
- Six COM Ports, 8 USB 2.0 ports
- One PCI-E x16, Two ISA, Four PCI Slots

Specifications

System	
CPU	Intel® Core™ 2 Quad, Core2 Duo Desktop Pentium Dual Core / Pentium D in the LGA775
FSB	1333/1066/800 MHz
BIOS	AMI BIOS with 8 Mb Flash EEPROM
System Chipset	Intel® G41 + ICH 7
I/O Chip	ITE IT8712F I/O Controller
System Memory	2 x 240-pin DDR3 DIMM sockets Dual-channel DDR3 1066/ 1333 SDRAM Max. up to 8 GB memory
Storage	1 x Parallel ATA IDE ports with UDMA 33, ATA-66/100 4 x Series ATA 300 ports
RAID	None
Watchdog Timer	None
H/W Status Monitor	Monitoring system temperature, voltage, and cooling fan status. Auto throttling control when CPU overheats
GPIO	Onboard programmable 8-bit Digital I/O interface
Expansion	1 x PCI Express x16, 2 x ISA 4 x PCI slots
MIO	
Internal I/O	1 x IrDA, 4 x RS-232, 1 x RS-232/422/485, 4 x USB 2.0
Back Panel I/O	1 x VGA, 1x LPT, 1 x Audio, 2 x RJ-45, 1 x RS-232, 4 x USB 2.0, 1 x KB, 1 x Mouse
Display	
Graphics Controller	Intel® integrated GMA X4500 Graphics
Display Memory	Intel® DVMT 4.0 supports up to 256 MB video memory
Resolution	Analog display : up to 2048 x 1536 @ 75Hz (QXGA)
Display Interface	DSUB-15 connector for VGA output
DVI	None

Audio	
HDAC	Realtek® ALC888 7.1 + HD audio codec
Audio Interface	Mic in, Line in, CD Audio in, Line out, Rear out and Center/Subwoofer out
Ethernet	
Controller	Dual Realtek® RTL 8111E PCIe Gigabit LAN Ethernet controllers
Ethernet Interface	IEEE 802.3 10BASE-T/100BASE-TX/1000BASE-T
Mechanical & Environmental	
Power Requirement	+3.3 V @ 4.73 A, +5 V @ 0.96 A, +12 V @ 9.11 A, -12 V @ 0.01 A, 5 VSB @ 0.07A
Power Type	24-pin ATX power connector, 1 x 4-pin ATX 12V power connector
FAN connector	1 x CPU, 2 x system with DC 12V
Operating Temperature	-10~60°C
Operating Humidity	10%~90% relative humidity, noncondensing
Size (L x W)	305 mm x 240 mm
Weight	1.44 lb (650 g)

Ordering Information

IM-G41DT

Alptech Elektronik GmbH



Zimmersmühlenweg 14-18
D-61440 Oberursel/Ts.

Tel.: 06171-9799110
Fax: 06171-9799115

E-Mail: info@alptech.de
www.alptech.de