

ODP-10T-XGA

10.4" open Frame TFT Monitor



Display Specifications

Display	10.4" Color Active TFT Flat Panel Display (Chimei G104x1-L01)
Luminance / Contrast Ratio	400 cd/m ² / 1200
Viewing Angle	176 (H) / 176 (V) degrees
Resolutions	1024x768 , 262K colors
Backlight Lifetime / Respose time	CCFL 2 tubes, 50,000 hrs / 10 ms
Touch Screen Description	Resistive (optional)
OSD Controls/Indicators	Automatic Screen, Setup (OSD), Brightness, Contrast, Horizontal/Vertical Position, Image Lock, Color Balance, Video Information, Power On and Sync
Power Input	DC 11-32 V, Phoenix 3 Pins Plug

Mechanical Specifications

Construction	Steel chassis & front panel
Dimensions (WxDxH)	236,8 x 178,9 x 39,2 mm
Weight	0.9kg (1.98 lbs)

Environment Specifications

Operating Temperature	0~50 °C (32~122 °F)
Storage Temperature	-20~60 °C (-4~140 °F)
Relative Humidity	10~90% @40 C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Certification	CE, FCC Class A

