

P2288C-MT



ALPTECH
Computer for Industry

Fanless 21.5" Wide-Screen Industrial Panel PC with Intel® Core i3/i5 Processor



Features

- **with the 6th/7th Gen. Intel Skylake-U/Kaby Lake-U CPU**
- 21.5" 1920 x 1080 FHD LCD Display w/ LED Backlight
- **Flat panel with projected capacitive touchscreen, 10 points Multi**
- Front panel compliant with IP65
- Anti-scratch surface: 7H hardness
- Easy Maintenance Design for HDD/SSD
- Serial Ports (RS-232/485), w/ Auto-flow Control
- Mini PCIe expansion slot support
- Fanless cooling system
- Low power consumption
- 12~24V Wide-Range DC Input
- **TPM 2.0 Header**

System

CPU	Intel® Core i5-6300U™ CPU 2.4GHz, Skylake Intel® Core i3-6100U™ CPU 2.3GHz, Skylake
Memory	4GB DDR4L SO-DIMM RAM module installed 2 x DDR4L SO-DIMM Socket, supporting 2133 MHz SDRAM up to 16GB
LAN	1 x Intel® I210AT 1x 219LM GbE controllers
Watchdog Timer	1~255 levels reset

Storage

1st Device	2 x 2.5" drive bay, Raid 0, 1, 5
2nd Device	mSATA, mPCIe

Audio

Speaker	No
---------	----

LCD Display

Size/Type	21.5" TFT LCD Panel
Max. Resolution	1920 x 1080, FHD
Max. Colors	16.2M
Luminance	300 cd/m²
Touch Screen	Projected capacitive touch panel, 10 points Multi
View Angle (U/D/R/L)	80°/80°/85°/85°

Power System

Power Input	DC 12~24V
-------------	-----------

Certification

EMC / EMI	Meet CE, FCC Class A
-----------	----------------------

Expansion

Expansion Bus	1 x Mini-card socket (Full Size)
---------------	----------------------------------

External I/O

Serial Ports	2 x RS-232 (4 x RS-232 optional)
USB Ports	4 x Type-A USB 3.0 ports 2x USB 2.0 port (4x USB 2.0 optional)
LAN	2 x RJ-45 GbE ports
Graphics	1 x HDMI / DP connector
WiFi	optional

Mechanical

Mounting Type	Panel Mounting and VESA-100 Mounting
Chassis	Panel-mounting chassis, aluminum front bezel and SECC steel chassis
Dimension (W x D x H)	536.00 x 58 x 332.00 mm
Weight (Net)	7 kg (15.4 lb)

Environmental

Operating Temp.	-10°C ~ 60°C
Storage Temp.	-30°C ~ 70°C (-22°F ~ 158°F)
Operating Humidity	10 ~ 95% RH @ 60°C (non-condensing)
Vibration	5 ~ 500Hz, 2Grms Random (with CFast/SSD)
Shock	Operating 10G, 11ms Non-operating 30G, 11ms (with CFast/SSD)

OS Support

W7 Pro / WS7E / W 10 Pro. / Linux: Ubuntu

ePPC Computer für Industrie
Computer for Industry



Dimensions

