

RPAD-819B 19" 8U Rack mount



IP 65 Front Frame

With 19" Color TFT Industrial Display Monitor



DESCRIPTION

The RPAD-819 19" Rack mount features an excellent viewing ability for monitoring and control applications. It is available with resistive touch screen that is easy to use and maintain.

The front panel of the display monitor is sealed with gasket for NEMA 4/IP 65 rating when it is panel-mounted in a NEMA rated cabinet or enclosure.

FEATURES

- 19" TFT SXGA LCD
- 1280(H)x1024(V), 300 cd/m
- Front Panel NEMA 4/IP 65 rating
- 19" Rackmount Type
- Resistive touch screen (optional)
- Optional DVI, Video or S-Video input
- Support wide-ranging resolutions from 640x 480 to up to 1280 x 1024 with auto phase and auto position



RPAD-819B 19" 8U Rack mount

| | |
|-----------------------------------|---|
| Display Specifications | |
| Display | 19" Color Active TFT Flat Panel Display |
| Luminance | 300 cd/m ² |
| Viewing Angle | 170/160 degrees (H/V) |
| Resolutions | 1280 x 1024 (native mode), 16.2M colors |
| Backlight Life | 50,000 hrs |
| Touch Screen (optional) | Resistive Touch Screen |
| OSD Controls/Indicators | Automatic Screen, Setup (OSD), Brightness, Contrast, Horizontal/Vertical Position Image Lock, Color Balance, Video Information, Power On and Sync Detection |
| Power Adapter | 11-28V DC 3-pin plug, Opt. ext. Power Adapter Input: 100~240V ⁺ .10% V AC, full ranging |
| Mechanical Specifications | |
| Construction | Steel chassis & Rackmount front panel |
| Dimensions | 483 (W) x 379 (H) x 68 (D) mm |
| Dimensions Cutout (W x H) | 449 (W) x 361 (H) mm |
| Weight | 6.53kgs |
| Environment Specifications | |
| Operating Temperature | 0~50° C(32~122° F) |
| Storage Temperature | -20~60 °C (-4~140 °F) |
| Relative Humidity | 10~90% @40 °C Non-condensing, without touch screen |
| Vibration | 1G peak, 5~500Hz (Random) |
| Shock | 15G peak acceleration (11 msec. duration) |
| Ratings | NEMA 4/IP65 compliant front panel |
| Certificate | Meet CE/FCC Class A |

Dimensions

483 (W) x 379 (H) x 68 (D) mm

